SMART SWITCH

PC ULTRA-THIN SERIES



1-Gang (L&N) Smart Wall Switch XZ-SAK101 XZ-WSAK101



Linkage







Control

2-Gang (L&N)

Smart Wall Switch

XZ-SAK102

XZ-WSAK102



Voice Control

3-Gang (L&N)

Smart Wall Switch

XZ-SAK103

XZ-WSAK103



2+2 (L&N) Scenario Smart Switch XZ-SAK122



Scenes Linkage





Timing







3+3(L&N)

Scenario Smart Switch

XZ-SAK133



Voice Control



Single Curtain Smart Switch XZ-SAK123 XZ-WSAK123



Linkage







Control



Scenario Setting

Mica White Titanium Gray Midnight Black Sandy Gold

Parameters:

- Rated Voltage: 250V∼
- Frequency: 50/60Hz μ
- Communication Protocol: ZigBee/Wi-Fi
- Rated Load:
- 1/2 Gang Switch 🔆 Max.800W/Gang
 - : Max.250W/Gang
 - Max.100W/Gang
- 3 Gang Switch A Max.800W/Gang
 - (Total Max.2200W)
 - ===== Max.250W/Gang
 - Max.100W/Gang
- Material: PC • Product Size: 86×86×31.7mm
 - (Thickness above the wall 6.7mm)

Parameters:

- Rated Voltage: 250V∼
- Frequency: 50/60Hz μ
- Communication Protocol: ZigBee
- 2 Gang+2 Scene A Max.800W/Gang
 - ≒ Max.250W/Gang
 - Max.100W/Gang
- 3 Gang+3 Scene ☼ Max.800W/Gang
 - (Total Max.2200W)
 - ≠ Max.250W/Gang
 - Max.100W/Gang
- Material: PC
- Product Size: 86×86×31.7mm

(Thickness above the wall 6.7mm)

Parameters:

- Rated Voltage: 250V∼
- Frequency:50/60Hz μ
- Communication Protocol: ZigBee/Wi-Fi
- Rated Load:Max. 300W
- Material: PC

Product Size:86 ×86×31.7mm

(Thickness above the wall 6.7mm)



4 Scenario Smart Switch XZ-SBK104 XZ-WSBK104

Scenes

Linkage

Remote

Control







6 Scenario

Smart Switch

XZ-SBK106



Parameters:

- Rated Voltage: 250V∼
- Frequency: 50/60Hz
- Communication Protocol: ZigBee/Wi-Fi
- Material: PC
- Product Size: 86×86×31.7mm

Mica White Titanium Gray Midnight Black Sandy Gold

(Thickness above the wall 6.7mm)

5